

Oilon Material Tolerance



Oilon Green Rod

Nominal Diameter	Tolerance in mm
50 - 56	+0.50 to +1.50
60 - 65 - 70	+0.50 to +1.80
75 - 80	+0.70 to +2.30
85 - 90	+1.00 to +2.70
100	+1.00 to +2.90
110	+1.00 to +3.30
120	+1.10 to +3.80
130 - 140	+1.10 to +4.10
150	+1.30 to +4.50
200	+0.20 to +7.00
250 - 300	+0.30 to +9.00

Oilon Sheet

Nominal Thickness	Tolerance in mm
10 - 12 - 16 - 20 - 25	+0.50 to +2.50
30 - 35 - 40 - 45 - 50	+0.50 to +3.00
55 - 60	+0.50 to +3.50
70 - 80 - 100	+0.50 to +4.50

Direct Plastics Ltd. Rother Valley Way, Holbrook, Sheffield, S20 3RW

The following information corresponds with our current knowledge and indicates our products and possible applications. We cannot give a legally binding guarantee of certain properties or the suitability for a specific application. Existing commercial patents must be observed. A definitive quality guarantee is given in our general conditions of sales. Unless otherwise stated, these values represent averages taken from injection moulding samples.

We reserve the right of technical alterations.