

PTFE

Material Tolerance



PTFE Natural Rod

Nominal Diameter	Tolerance in mm
4 - 5 - 6 - 8	-0 to +0.6
10 - 12	-0 to +6%
15	-0 to +6%
20 - 22 - 25 - 30	-0 to +6%
35 - 40 - 45	-0 to +6%
50 - 55 - 60 - 65 - 70	-0 to +6%
75 - 80 - 90 - 100 - 110 - 120	-0 to +6%

PTFE Natural Sheet

Nominal Thickness	Tolerance in mm
0.25 - 0.5	-0 to +10%
1 - 1.5	-0 to +0.15
2	-0 to +0.3
3	-0 to +0.45
4	-0 to +0.6
5	-0 to +0.75
6 - 8 - 10 - 12	-0 to +15%
15 - 20 - 25 - 30	-0 to +15%
40 - 50	-0 to +15%

Direct Plastics Ltd. Rother Valley Way, Holbrook, Sheffield, S20 3RW

The following information corresponds with our current knowledge and indicates our products and possible applications. We cannot give a legally binding guarantee of certain properties or the suitability for a specific application. Existing commercial patents must be observed. A definitive quality guarantee is given in our general conditions of sales. Unless otherwise stated, these values represent averages taken from injection moulding samples.

We reserve the right of technical alterations.