

PVC Material Tolerance



PVC Grey Rod

| Nominal Diameter | Tolerance in mm |
|------------------------|-----------------|
| 6 | +0.10 to +0.40 |
| 8 | +0.10 to +0.50 |
| 10 | +0.10 to +0.60 |
| 12 | +0.20 to +0.70 |
| 15 | +0.20 to +0.80 |
| 18 | +0.20 to +0.90 |
| 20 - 22 - 25 - 30 - 32 | +0.20 to +1.20 |
| 35 | +0.20 to +1.30 |
| 40 | +0.20 to +1.50 |
| 45 - 50 - 55 | +0.30 to +2.00 |
| 60 | +0.30 to +2.30 |
| 65 - 70 | +0.30 to +2.50 |
| 75 - 80 | +0.40 to +3.00 |
| 90 | +0.50 to +3.00 |
| 100 | +0.60 to +3.50 |
| 110 | +0.70 to +4.00 |
| 120 | +0.80 to +5.00 |
| 130 | +0.90 to +6.00 |
| 140 | +1.00 to +7.00 |
| 150 | +1.10 to +8.00 |
| 160 | +1.20 to +9.00 |
| 180 | +1.30 to +10.00 |
| 200 - 225 - 250 | +1.50 to +11.00 |
| 300 | +1.50 to +12.00 |

Direct Plastics Ltd. Rother Valley Way, Holbrook, Sheffield, S20 3RW

The following information corresponds with our current knowledge and indicates our products and possible applications. We cannot give a legally binding guarantee of certain properties or the suitability for a specific application. Existing commercial patents must be observed. A definitive quality guarantee is given in our general conditions of sales. Unless otherwise stated, these values represent averages taken from injection moulding samples. We reserve the right of technical alterations.

PVC Material Tolerance



PVC Grey Sheet

| Nominal Thickness | Tolerance in mm |
|-------------------|-----------------|
| 1.5 | -0.15 to +0.15 |
| 2 | -0.17 to +0.17 |
| 3 | -0.20 to +0.20 |
| 4 | -0.22 to +0.22 |
| 5 | -0.26 to +0.26 |
| 6 | -0.28 to +0.28 |
| 8 | -0.35 to +0.35 |
| 10 | -0.41 to +0.41 |
| 12 | -0.48 to +0.48 |
| 15 | -0.56 to +0.56 |
| 20 | -0.70 to +0.70 |
| 25 | -0.85 to +0.85 |
| 30 | -1.00 to +1.00 |
| 40 | -1.30 to +1.30 |
| 50 | -1.60 to +1.60 |

Direct Plastics Ltd. Rother Valley Way, Holbrook, Sheffield, S20 3RW

The following information corresponds with our current knowledge and indicates our products and possible applications. We cannot give a legally binding guarantee of certain properties or the suitability for a specific application. Existing commercial patents must be observed. A definitive quality guarantee is given in our general conditions of sales. Unless otherwise stated, these values represent averages taken from injection moulding samples. We reserve the right of technical alterations.